

KENWOOD

Compact Synthesized FM Portable Radios

TK-260G/360G



- SIMPLE OPERATION
- MULTI-MODE WIDE/NARROW BANDWIDTH PER CHANNEL
- WEATHER-RESISTANT SEALS
- COMPANDED AUDIO
- PTT ID PER CHANNEL
- BUILT-IN QT/DQT
- DTMF AND 2-TONE
- DIE-CAST CHASSIS
- UP TO 8-CHANNEL CAPACITY
- FLASH MEMORY ADVANTAGE
- MIL-STD 810 C/D/E

The Next Generation in Portables



Productivity takes a giant leap forward as performance is combined with extra operating ease and versatility. Along with world-class reliability, the TK-260G/360G incorporates superior features such as multi-mode wideband operation, high-fidelity audio, and PTT unit ID (digital ANI option modules). When you need the best premium radio product can provide, the choice is obvious.

Elements of a Premium Radio Product

STRENGTH & DURABILITY

Kenwood's facilities are proud to be internationally recognized as ISO-9001 certified and this means that our radio products follow a strict adherence to high standards in design, manufacturing and quality assurance. Whatever the requirement, the excellent performance and reliability of our communications equipment — exemplified by the TK-260G/360G portables — make Kenwood the premier choice.

MIL-STD 810 C/D/E

The TK-260G/360G are manufactured along Kenwood's demanding technical and industrial standards, meeting or exceeding the tough environmental standards used by the U.S. Department of Defense.

DIE-CAST CHASSIS AND POLYCARBONATE CASE

The monocoque aluminum die-cast chassis-heat sink borrows a principal from aircraft construction for rigid strength. Surrounding this and forming an integral part of the chassis, is the super-tough polycarbonate case to provide years of durability. The heavy-duty belt clip and antenna mount are also integrated into the chassis for strengthened unit construction.



WEATHER-RESISTANT

Integrated elements like gasket seals and the polyvinyl speaker cone prevent moisture penetration for confident wet weather use.

PERFORMANCE

A premium radio design like the TK-260G/360G portables use state-of-the-art surface mount technology, multiple layer epoxy PC boards, high-level integrated circuits and hybrid components to create a symphony of compact, rugged and power-efficient performance.

COMPANDED AUDIO

The compander noise-reduction feature enhances audio clarity on narrow bandwidth systems and is programmable per channel. Voice intelligence components are amplified and compressed at the transmit end then re-expanded on the receive end to reproduce the original audio signal.

ure Performance

enhancements in the TK-260G/360G deliver famous Kenwood quality, this rugged unit wide/narrow bandwidth (per channel), compounded by your operations need a boost that only a us — Kenwood.



HEAVY-DUTY ANTENNA MOUNT

The antenna's industry-standard SMA connector provides improved mechanical and electrical performance.

HIGH OUTPUT AUDIO

A large 1-3/4 inch speaker provides 500 mW audio output. This enables the user to hear transmissions clearly even in the noisiest environments.

EASY USER INTERFACE

A premium radio product must be easy to setup, use and maintain. The TK-260G/360G is a perfect example of this philosophy as it combines user-friendly ergonomics in a lightweight and well-balanced package.

BUILT-IN QT AND DQT SIGNALING

Encoder/decoder function segregates talk groups so users only hear calls from their own group.

SIGNALING AND/OR LOGIC

For improved response when using combinations of signaling systems, squelch is opened when either one, or all, signal requirements are met.

BUSY CHANNEL LOCKOUT

Lockout further improves channel management by preventing transmission if another talk group is already on the air.

BUILT-IN 2-TONE DECODER AND ENCODER

The decoder and encoder functions offer a 2-tone paging code assignable to any channel. An incoming message is signaled with audible and visible alerts.

TWO-COLOR LED

The two-color LED provides traditional transmit/warning (red), receive (green), and alert (orange) visual indications. This LED is recessed to limit omni-directional visibility to everyone except the radio operator.



VERSATILITY

A premium radio like the TK-260G/360G must be flexible enough to answer any application and offer the room to expand as system or user needs grow.

POWER OUTPUT SETTINGS

High/Low settings can be input for each channel by your dealer. The TK-260G can be set for 5W/1W and the TK-360G for 4W/1W.

FLASH MEMORY ADVANTAGE

Flash memory permits updates, advanced feature sets and system architectural changes to be made electronically without ever opening the unit. This means fast changes for the system operator and less down time for users.

WIDE/NARROW CHANNEL BANDWIDTH

The TK-260G/360G can be programmed for wide or narrow bandwidth operation per channel to accommodate all channel allocations now and in the future.

MAXIMUM 8-CHANNEL MEMORY

On-board memory stores frequency and configuration settings that can be programmed using a personal computer. The mechanical encoder utilizes a special pin for the setting of 2-, 4-, 6- or a maximum of 8-channel (default) capacity for customized performance.

PC PROGRAMMING AND TUNING

Radio parameter programming and tuning can be accomplished via the accessory connector from a PC-compatible computer without ever having to open the radio to save both time and expense (requires optional programming cable and software).

DTMF ANI FUNCTION

A DTMF code can be encoded by two methods: "PTT ID" or "DIAL ID" operation. "PTT ID" — the traditional DTMF ANI unit ID — is programmable per channel and sends ANI automatically on every PTT (begin of transmit leading edge code and EOT trailing edge code are both independently programmable). Additionally, each channel can have its own unique DTMF ANI number to suit a variety of custom applications. Dial ID permits sending the DTMF ANI codes (BOT or EOT codes) manually via the front keypad for remote control or system-access applications.

EMBEDDED MESSAGE

The radio's flash memory can store an electronic message containing owner identification, property I.D. numbers, user and department names, service records, etc. A radio can be electronically identified even if external labels, markings or factory serial numbers have been removed..

OTHER FEATURES

■ TIME-OUT TIMER ■ BATTERY POWER SAVE ■ LOW BATTERY ALERT
■ MONITOR/VOLUME SET ■ BUSY LED CONTROL

The image displays a variety of Motorola accessories for mobile communication devices. On the left, there are three types of batteries (KNB-14, KNB-15A, KNB-15), two charging options (KSC-15, KSC-16), and a conditioning battery charger (KSC-21R). In the center, there are three vehicle chargers (KVC-3, KVC-4), two speaker microphones (KMC-17, KMC-21), and two earphone kits (KEP-2, KEP-3). To the right of these are three different headsets (KHS-7, KHS-7A, KHS-8BL, KHS-8BE, KHS-9BL, KHS-9BE). Further right are three antennas (KRA-14, KRA-15, KRA-16) and three carrying options (KRB-8, KLB-70, KLB-6SW, KLB-8DS, KLB-8S, KLB-8L). At the bottom right, there is a water-resistant bag (KWR-1).

	TK-260G	TK-360G
GENERAL		
Frequency range	150 ~ 174 MHz	450 ~ 470 MHz
Number of channels	Max. 8	Max. 8
Channel spacing Wide/Narrow	25, 30 kHz / 12.5, 15 kHz	25 kHz / 12.5 kHz
PLL step	2.5, 5, 6.25, 7.5 kHz	5, 6.25 kHz
Channel frequency spread	24 MHz	20MHz
Antenna impedance	50 Ω	50 Ω
Operating voltage	7.5 V DC (±20%)	7.5 V DC (±20%)
Battery life (5-5-90 duty cycle with battery saver off) with KNB-14 (600mAh) with KNB-15A (1100mAh)	More than 4 hours More than 8 hours	More than 4 hours More than 8 hours
Operating temperature range	-22° F ~ +140° F (-30° C ~ +60° C)	-22° F ~ +140° F (-30° C ~ +60° C)
Frequency stability	± 3 ppm (-22° F ~ +140° F) (-30° C ~ +60° C)	± 2.5 ppm (-22° F ~ +140° F) (-30° C ~ +60° C)
Dimensions (W x H x D)	2-5/16 x 5-5/16 x 1-1/4 in. (58 x 135 x 32 mm) with KNB-14 battery 2-5/16 x 5-5/16 x 1-3/8 in. (58 x 135 x 35 mm) with KNB-15A battery	2-5/16 x 5-5/16 x 1-1/4 in. (58 x 135 x 32 mm) with KNB-14 battery 2-5/16 x 5-5/16 x 1-3/8 in. (58 x 135 x 35 mm) with KNB-15A battery
Weight (net)	0.49 lbs. (220 g), main body only without antenna 0.88 lbs. (400 g) with KNB-14 battery & antenna	0.49 lbs. (220 g), main body only without antenna 0.88 lbs. (400 g) with KNB-14 battery & antenna
FCC ID	ALH29463110	ALH29473110
FCC compliance	FCC parts 22, 74, 80, 90, 95	FCC parts 22, 74, 80, 90, 95
IC certification	282195581A	282195580A

Kenwood follows a policy of continuous advancement in development. For this reason specifications may be changed without notice.

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures
Rain	506.1/Procedure II	506.2/Procedure II	506.3/Procedure II
Humidity	507.1/Procedure II	507.2/Procedure II	507.3/Procedure II
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV

14-6, 1-chome, Dogenzaka, Shibuya-ku, Tokyo 150-8501, Japan
KENWOOD COMMUNICATIONS CORPORATION
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745, U.S.A.
KENWOOD ELECTRONICS CANADA INC.
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8



Communications Equipment Division
Kenwood Corporation
ISO9001 certification

This has been printed on recycled paper
CL264KP-E-4(00) 991015B Printed in Japan